Bay Area Air Quality Management District

939 Ellis Street San Francisco, CA 94109 (415) 771-6000

Final

MAJOR FACILITY REVIEW PERMIT

U.S. Pipe and Foundry Company Facility #A0083

Facility Address:

1295 Whipple Road Union City, CA 94587

Mailing Address:

1295 Whipple Road Union City, CA 94587

Responsible Official

James E. Kelly, Plant Manager 510) 441-5814

Facility Contact

Rodney M. Helfrich, Environmental Engineer (510) 441-5865

Ductile Iron Foundry

Primary SIC: 3321

Product: Ductile Iron Pressure Pipe

ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT

Signed by Ellen Garvey	July 1, 1997
Ellen Garvey, Air Pollution Control Officer	Date

TABLE OF CONTENTS

I.	STANDARD CONDITIONS	1
II.	EQUIPMENT LIST	5
	A. PERMITTED SOURCE LIST	5
	B. BATEMENT DEVICE LIST	6
III.	GENERAL APPLICABLE REQUIREMENTS	7
IV.	SOURCE-SPECIFIC APPLICABLE REQUIREMENTS	9
V.	SCHEDULE OF COMPLIANCE	21
VI.	PERMIT CONDITIONS	21
	A. SOURCE SPECIFIC PERMIT CONDITIONS	21
	B. FACILITY-WIDE PERMIT CONDITIONS	27
VII.	APPLICABLE EMISSION LIMITS & COMPLIANCE MONITORING REQUIREMENTS	28
VIII.	TEST METHODS	40
IX.	GLOSSARY	42
X.	APPENDIX A - STATE IMPLEMENTATION PLAN	46

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

I. STANDARD CONDITIONS

A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

BAAQMD Regulation 1 - General Provisions and Definitions

(as amended by the District Board on 11/3/93);

SIP Regulation 1 - General Provisions and Definitions

(as approved by EPA through 11/10/82);

BAAQMD Regulation 2, Rule 1 - Permits, General Requirements

(as amended by the District Board on 6/7/95);

SIP Regulation 2, Rule 1 - Permits, General Requirements

(as approved by EPA through 6/23/95);

BAAQMD Regulation 2, Rule 2 - Permits, New Source Review

(as amended by the District Board on 6/7/95);

SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration

(as approved by EPA through 10/19/84); and

BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking

(as amended by the District Board on 6/15/94).

B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

- 1. This Major Facility Review Permit expires on July 1, 2002. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than January 1, 2002, and no earlier than July 1, 2001. **If a complete application for renewal has not been submitted in accordance with these deadlines, the facility may not operate after** June 30, 2002. (Regulation 2-6-307, 404.2, & 409.6; MOP Volume II, Part 3, §4.2)
- 2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
- 3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part 3, §4.11)
- 4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

I. Standard Conditions (continued)

- 5. The filing of a request by the facility for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
- 6. This permit does not convey any property rights of any sort, nor any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
- 7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
- 8. Any records required to be maintained pursuant to this permit which the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
- 9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B Public Information, Confidentiality of Business Information. (40 CFR Part 2)
- 10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)

C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment which is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

E. Records

Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of entry. (Regulation 2-6-501, Regulation 3; MOP Volume II, Part 3, §4.7)

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

I. Standard Conditions (continued)

F. Monitoring Reports

All required monitoring reports must be submitted to the District at least once every six months. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported to the District's Compliance and Enforcement Division within 10 days of the discovery of the incident. Within 30 days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. (Regulation 2-6-502, Regulation 3; MOP Volume II, Part 3, §4.7)

G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms. The certification should be directed to the District's Compliance and Enforcement Division, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

Director of the Air Division USEPA, Region IX 75 Hawthorne Street San Francisco, CA 94105 Attention: Air-3

(MOP Volume II, Part 3, §4.5 and 4.15)

H. Emergency Provisions

- 1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
- 2 The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit caused by conditions beyond the permit holder's reasonable control by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq.

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

I. Standard Conditions (continued)

Any variance granted by the Hearing Board from any term or condition of this permit which lasts longer than 90 days will be subject to EPA approval. (MOP Volume II, Part 3, §4.8)

3. Notwithstanding the foregoing, the granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement unless the Major Facility Review Permit has been modified pursuant to Regulation 2, Rule 6. (MOP Volume II, Part 3, §4.8)

I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

J. Accidental Release

This facility is subject to 40 CFR Part 68, Chemical Accident Prevention Provisions. The permit holder shall submit a risk management plan (RMP) by the date specified in §68.10. The permit holder shall also certify compliance with the requirements of Part 68 as part of the annual compliance certification, as required by Regulation 2, Rule 6. (40 CFR Part 68, Regulation 2, Rule 6)

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

II. EQUIPMENT LIST

A. Permitted Source List

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2-1-302.

Table II-A

S-#	Description	Make or Type	Model	Capacity
S-1	Cupola (coke)	U.S. Pipe	None	55 ton/hr, 182 MM BTU/hr
S-4	Ductile Treating Unit	U.S. Pipe	None	55 ton/hr,
S-5	Ladle Lancing	U.S. Pipe	None	40 ton/hr
S-7	Mold Sandblast	Pauli & Griffin	24S	0.4 ton/hr
S-8	Bell Blowout	U.S. Pipe	None	38 ton/hr
S-15	Annealing Oven (natural gas, liquid petroleum gas)	U.S. Pipe	None	55 ton/hr, 88 MM BTU/hr
S-16	Pneumatic Cement Transport System	U.S. Pipe	None	32.5 ton/hr
- S-17	Surface Coater	Unknown	Unknown	Unknown
S-26	Paint Storage Tank #1	Underground, Fixed-Roof	Unknown	10,000 gallon
IS-27	Paint Storage Tank #2	Underground, Fixed-Roof	Unknown	10,000 gallon
S-32	Pneumatic Dust Transport System	U.S. Pipe	None	1.3 ton/hr
S-33	Gasoline Dispensing Facility, non-retail (GDF#7675)	Unknown	Unknown	1 nozzle
S-40	Portable Abrasive Blasting Unit #1	P & G	Unknown	740 lb/hr
S-41	Portable Abrasive Blasting Unit #2	Clemco	Unknown	450 lb/hr
S-32000	Miscellaneous Fuel Burning Sources	U.S. Pipe	Unknown	Unknown

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

xpiration Date: 7-1-02 ID: DTJ

II. Equipment List (Continued)

B. Abatement Device List

Table II-B

		Source(s)	Applicable	Operating	Required
A-#	Description	Controlle	Requirement	Parameters	Efficiency
	2.000	d	and discount	2 412 412 412 412	21110101101
A-3	Cupola Afterburner	S-1	District Cond	Minimum operating	None
	(natural gas, liquid	Cupola	#2274, part 3	temperature of	
	petroleum gas)	_		1550°F	
A-5	Mold Sandblast Baghouse	S-7 Mold	BAAQMD	None	Grain
		Sandblast	Reg. 6-310		loading not
					to exceed
					0.15 gr/dscf
A-9	Pneumatic Cement	S-16	BAAQMD	None	grain
	Transport Baghouse	Pneumatic	Reg. 6-310		loading not
		Cement			to exceed
		Transport			0.15 gr/dscf
A-10	Ductile Treater Baghouse	S-4	BAAQMD	None	grain
		Ductile	Reg. 6-301		loading not
		Treating			to exceed
		Units			0.15 gr/dscf
A-12	Cupola Baghouse	S-1	District Cond	Pressure drop	None
		Cupola &	#2274, part 4	across bags not to	
		S-5 Ladle		exceed 6 inches	
		Lancing &		water column	
		S-6 Brick			
		Saw			
A-19	Dust Collector	S-32	District	None	grain
		Pneumatic	Condition		loading
		Dust	#2676, part 3		shall not
		Transport			exceed 0.10
					gr/dscf
A-20	Bell Blowout Dust	S-8 Bell	District	Pressure drop	None
	Collector	Blowout	Condition	across bags not to	
			#2212, part 2	exceed 6 inches	
				water column	

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

III. GENERAL APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements would not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit.

The dates in parenthesis in the Title column identify the versions of the regulations being cited and are, as applicable:

- BAAQMD regulation(s):
 The date(s) of adoption or most recent amendment of the regulation by the District Board
- 2. Any federal requirement, including a version of a District regulation that has been approved into the SIP:

The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

Where an applicable requirement is a SIP requirement, the full language of the SIP requirement is included in Appendix A of this permit.

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 1	General Provisions and Definitions (11/3/93)	N
SIP Regulation 1	General Provisions and Definitions (11/10/82)	Y
BAAQMD Regulation 4	Air Pollution Episode Plan (3/20/91)	N
SIP Regulation 4	Air Pollution Episode Plan (8/06/90)	Y
BAAQMD Regulation 5	Open Burning (11/2/94)	N

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

ID: DTJ

III. General Applicable Requirements (continued)

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
SIP Regulation 5	Open Burning (5/3/84)	Y
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	N
SIP Regulation 6	Particulate Matter and Visible Emissions (5/3/84)	Y
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds - General Provisions (6/15/94)	Y
BAAQMD Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (12/20/95)	N
SIP Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (11/16/83)	Y
BAAQMD Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (3/22/95)	Y
BAAQMD Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (12/20/95)	N
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants - Sulfur Dioxide (3/15/95)	N
SIP Regulation 9, Rule 1	Inorganic Gaseous Pollutants - Sulfur Dioxide (5/3/84)	Y
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants - Asbestos Demolition, Renovation and Manufacturing (12/4/91)	Y
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (7/11/90)	N
SIP Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (9/2/81)	Y

Expiration Date: 7-1-02

ID: DTJ

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parenthesis in the Title column identify the versions of the regulations being cited and are, as applicable:

- BAAQMD regulation(s):
 The date(s) of adoption or most recent amendment of the regulation by the District Board
- 2. Any federal requirement, including a version of a District regulation that has been approved into the SIP:

The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. Additionally, where an applicable requirement is a SIP requirement, the full language of the SIP requirement is included in Appendix A of this permit. All other text may be found in the regulations themselves.

Table IV-A S-1 Cupola

Applicable	Regulation Title or	Federally Enforceable	Future Effective
Requirement	Description of Requirement	(Y/N)	Date
BAAQMD	Particulate Matter and Visible Emissions (7/11/90)		
Regulation 6			
6-301	Ringelmann No.1 Limitation	N	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No.1 Limitation	Y^1	

This section of the SIP rule has been removed from or revised in the current BAAQMD rule. Nevertheless, the source must comply with this SIP requirement until US EPA has reviewed and approved the District's revision of the regulation.

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

on Date: 7-1-02 ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

Table IV-A (continued) S-1 Cupola

		Federally	Future
Applicable	Regulation Title or	Enforceable	Effective
Requirement	Description of Requirement	(Y/N)	Date
BAAQMD	Sulfur Dioxide (3/15/95)		
Regulation			
9, Rule 1			
9-1-301	Limitations on Ground Level Concentrations	N	
9-1-302	General Emission Limitation	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation	Inorganic Gaseous Pollutants - Sulfur Dioxide (5/3/84)		
9, Rule 1			
9-1-301	Limitations on Ground Level Concentrations	Y	
BAAQMD	Lead (3/17/82)		
Regulation			
11, Rule 1			
11-1-301	Daily Limitation	Y	
11-1-302	Ground Level Concentration Without Background	Y	
BAAQMD			
Condition			
#2274			
part 1	A-3 Afterburner and A-12 Baghouse Abatement Requirement	Y	
. 2	(basis: cumulative increase)	***	
part 2	Limitation on Daily Hours of Operation	Y	
	(basis: cumulative increase)	\$7	
part 3	Minimum A-3 Afterburner Combustion Chamber Temperature	Y	
mont 1	(basis: cumulative increase)	V 7	
part 4	A-12 Baghouse maintenance requirement	Y	
part 5	(basis: cumulative increase) A-3 Afterburner temperature monitor and recorder	Y	
part 5	(basis: cumulative increase)	1	
part 6	Recordkeeping Requirement (basis: cumulative increase)	Y	
part 7	SO2 monitoring (Regulation 9-1-301, Regulation 2-6-501)	Y	
part 8	Baghouse maintenance (Regulation 6-301, Regulation 2-6-501)	Y	
part 9	Visible emissions monitoring (Regulation 6-301, Regulation 2-	Y	
part	6-501)	1	
	0-301)		

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

Table IV-B S-4 Ductile Treating Unit

		Federally	Future
Applicable	Regulation Title or	Enforceable	Effective
Requirement	Description of Requirement	(Y/N)	Date
BAAQMD	Particulate Matter and Visible Emissions (7/11/90)		
Regulation 6	District of the second	N	
6-301	Ringelmann No.1 Limitation	N	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	1	
6-301	Ringelmann No.1 Limitation	Y ¹	
BAAQMD	Sulfur Dioxide (3/15/95)		
Regulation			
9, Rule 1			
9-1-301	Limitations on Ground Level Concentrations	N	
9-1-302	General Emission Limitation	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation	Inorganic Gaseous Pollutants - Sulfur Dioxide (5/3/84)		
9, Rule 1			
9-1-301	Limitations on Ground Level Concentrations	Y	
BAAQMD	Lead (3/17/82)		
Regulation			
11, Rule 1			
11-1-301	Daily Limitation	Y	
11-1-302	Ground Level Concentration Without Background	Y	
BAAQMD			
Condition			
#1783		***	
part 1	Sulfur Dioxide Mass Emission Limit (basis: cumulative	Y	
	increase)	V	
part 2	A-10 Baghouse Abatement Requirement (basis: cumulative increase)	Y	
		V	
part 3	A-10 pressure differential gauge (basis: cumulative increase)	Y	
part 4	A-10 Baghouse discharge requirement (basis: Regulation 6-	Y	
nort 5	301)	V	
part 5	A-10 Baghouse maintenance requirement	Y	
mant 6	(basis: cumulative increase)		
part 6	Baghouse maintenance (Regulation 6-301, Regulation 2-6-501)	Y	
part 7	Visible emissions monitoring (Regulation 6-301, Regulation 2-	Y	
	6-501)		

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

This section of the SIP rule has been removed from or revised in the current BAAQMD rule. Nevertheless, the source must comply with this SIP requirement until US EPA has reviewed and approved the District's revision of the regulation.

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

Table IV-C S-5 Ladle Lancing

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (7/11/90)		
6-301 6-305	Ringelmann No.1 Limitation Visible Particles	N Y	
6-310 6-311	Particulate Weight Limitation General Operations	Y Y	
SIP Regulation 6	PROVISIONS NO LONGER IN CURRENT RULE Particulate Matter and Visible Emissions (12/19/90)		
6-301 BAAQMD Condition #14989	Ringelmann No.1 Limitation	Y ^l	
part 1	Baghouse maintenance (Regulation 6-301, Regulation 2-6-501)	Y	
part 2	Visible emissions monitoring (Regulation 6-301, Regulation 2-6-501)	Y	

This section of the SIP rule has been removed from or revised in the current BAAQMD rule. Nevertheless, the source must comply with this SIP requirement until US EPA has reviewed and approved the District's revision of the regulation.

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

Table IV-D S-8 Bell Blowout

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD	Particulate Matter and Visible Emissions (7/11/90)		
Regulation 6			
6-301	Ringelmann No.1 Limitation	N	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No.1 Limitation	\mathbf{Y}^1	
BAAQMD			
Condition			
#2212			
part 1	A-17 Baghouse Abatement Requirement	Y	
	(basis: cumulative increase)		
part 2	A-17 Baghouse maintenance requirement	Y	
	(basis: cumulative increase)		
part 3	A-17 Baghouse pressure drop gauge (basis: cumulative	Y	
	increase)		
part 4	Visible emissions monitoring (Regulation 6-301, Regulation 2-	Y	
	6-501)		

This section of the SIP rule has been removed from or revised in the current BAAQMD rule. Nevertheless, the source must comply with this SIP requirement until US EPA has reviewed and approved the District's revision of the regulation.

Final Permit for Facility #: A0083

Expiration Date: 7-1-02 ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

Table IV-E S-15 Annealing Oven

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD	Particulate Matter and Visible Emissions (7/11/90)		
Regulation 6			
6-301	Ringelmann No.1 Limitation	N	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No.1 Limitation	\mathbf{Y}^1	
BAAQMD	Sulfur Dioxide (3/15/95)		
Regulation			
9, Rule 1			
9-1-301	Limitations on Ground Level Concentrations	N	
9-1-302	General Emission Limitation	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation	Inorganic Gaseous Pollutants - Sulfur Dioxide (5/3/84)		
9, Rule 1			
9-1-301	Limitations on Ground Level Concentrations	Y	
BAAQMD			
Condition			
#14990			
part 1	Visible emissions monitoring (Regulation 6-301, Regulation 2-6-501)	Y	

This section of the SIP rule has been removed from or revised in the current BAAQMD rule. Nevertheless, the source must comply with this SIP requirement until US EPA has reviewed and approved the District's revision of the regulation.

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

Table IV-F S-16 Pneumatic Cement Transport System

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD	Particulate Matter and Visible Emissions (7/11/90)		
Regulation 6			
6-301	Ringelmann No.1 Limitation	N	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No.1 Limitation	\mathbf{Y}^{1}	
BAAQMD Condition #14991			
part 1	Visible emissions monitoring (Regulation 6-301, Regulation 2-6-501)	Y	

This section of the SIP rule has been removed from or revised in the current BAAQMD rule. Nevertheless, the source must comply with this SIP requirement until US EPA has reviewed and approved the District's revision of the regulation.

Table IV-G S-17 Surface Coater

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 19	Surface Coating of Miscellaneous Metal Parts and Products		
8-19-302	Limits	Y	
8-19-313	Spray Application Equipment Limitations	Y	
8-19-320	Solvent Evaporative Loss Minimization	Y	
8-19-501	Records	N	

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

Table IV-H S-26 Paint Storage Tank #1 S-27 Paint Storage Tank #2

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD	Storage of Organic Liquids (1/1/93)		
Regulation			
8, Rule 5			
8-5-301	Standards - Storage Tanks Smaller than 150m ³	Y	
8-5-328	Tank Cleaning Requirements	Y	
8-5-501	Records	Y	

Table IV-I S-32 Pneumatic Dust Transport System

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (7/11/90)		
6-301	Ringelmann No.1 Limitation	N	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No.1 Limitation	Y^1	
BAAQMD Condition #2676			
part 1	A-19 Baghouse Abatement Requirement (basis: cumulative increase)	Y	
part 2	Limitation on Daily hours of operation (basis: cumulative increase)	Y	
part 3	A-19 Baghouse Grain Loading Limit (basis: BACT)	Y	
part 4	Automatic shutdown (Regulation 6-301, Regulation 2-6-501)	Y	

This section of the SIP rule has been removed from or revised in the current BAAQMD rule. Nevertheless, the source must comply with this SIP requirement until US EPA has reviewed and approved the District's revision of

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

the regulation.

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

Table IV-J S-33 Gasoline Dispensing Facility (Non-Retail)

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 7	Organic Compounds - Gasoline Dispensing Facilities (6/1/94)		
8-7-112	Phase II Exemptions	Y	
8-7-112.7	Exemption - Older Facilities with Low Annual Throughput	Y	
8-7-113	Tank Gauging and Inspection Exemption	Y	
8-7-114	Stationary Tank Testing Exemption	Y	
8-7-301	Phase I Requirements	Y	
8-7-301.1	Requirement for CARB Phase I System	Y	
8-7-301.2	Installation of Phase I Equipment per CARB Requirements	Y	
8-7-301.3	Submerged Fill Pipes	Y	
8-7-301.4	P-V Valves on All Open Vent Pipes	Y	
8-7-301.5	Maintenance of Phase I Equipment per Manufacturers Guidelines	Y	
8-7-301.6	Leak-Free, Vapor-Tight	Y	
8-7-301.7	Poppetted Drybreaks	Y	
8-7-303	Topping Off	Y	
8-7-304	Certification Requirements	Y	
8-7-308	Operating Practices	Y	
8-7-312	Removal of Gasoline	Y	
8-7-401	Equipment Installation and Modification	Y	
8-7-404	Certification of New Installations	Y	
8-7-501	Burden of Proof	Y	
8-7-502	Right of Access	Y	
BAAQMD Condition			
#708			
part 1	Annual throughput (basis: Regulation 8-7-112.7)	Y	

Final Permit for Facility #: A0083

Expiration Date: 7-1-02 ID: DTJ

IV. Source-Specific Applicable Requirements (continued)

Table IV-K S-40 Portable Abrasive Blasting Unit #1 S-41 Portable Abrasive Blasting Unit #2

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD	Sandblasting (7/11/90)	(
Regulation			
12, Rule 4			
12-4-301	Ringelmann 1 Limitation	N	
12-4-302	Ringelmann 2 Limitation	Y	
12-4-305	Performance Standards for Abrasives	Y	
12-4-306	Certification of Abrasives	Y	
SIP	PROVISIONS NO LONGER IN CURRENT RULE		
Regulation	Miscellaneous Standards of Performance		
12, Rule 4	Sandblasting (12/4/79)		
12-4-301	Ringelmann Number 1 Limitation	Y	
12-4-304	Performance Standards for Other Abrasive Blasting	Y	
BAAQMD Condition #13321			
part 1	Material Throughput Limitation (basis: cumulative increase)	Y	
part 2	Blast Media Type (basis: cumulative increase)	Y	
part 3	Daily Material Throughput Recordkeeping Requirement (basis: cumulative increase)	Y	

This section of the SIP rule has been removed from or revised in the current BAAQMD rule. Nevertheless, the source must comply with this SIP requirement until US EPA has reviewed and approved the District's revision of the regulation.

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

V. SCHEDULE OF COMPLIANCE

The permit holder shall continue to comply with all applicable requirements cited in Parts III and IV of this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit.

VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

A. Source Specific Permit Conditions

Condition #2274:

For S-1 Cupola

- 1. Source S-1 Cupola shall not be operated unless it is abated by A-3 Afterburner and A-12 Baghouse. (basis: cumulative increase)
- 2. S-1 Cupola shall not be operated more than 11 hours per day. (basis: cumulative increase)
- 3. A-3 Afterburner combustion chamber temperature shall not operate below 1550 degrees Fahrenheit whenever S-1 Cupola is in operation. (basis: cumulative increase)
- 4. The A-12 Baghouse cloth filter bags shall be cleaned or replaced when the pressure drop across the bags exceeds 6 inches water column. (basis: cumulative increase)
- 5. The owner/operator of A-3 shall install and maintain a continuous temperature monitor and recorder to verify the A-3 Afterburner combustion chamber temperature. (basis: cumulative increase)
- 6. The owner/operator of S-1 shall maintain records of the daily hours of operation of S-1 and A-3 combustion chamber temperature in a District-approved log. The records shall be retained on site for a minimum of five years

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VI. Permit Conditions (continued)

A. Source Specific Permit Conditions (continued)

from the date of entry and made available to District representatives upon request. (basis: cumulative increase, BAAQMD Regulation 2-6-501)

Condition #2274:

For S-1 Cupola

7. The sulfur content of the coke used at S-1, Cupola, shall not exceed 1.0 percent as a surrogate means for ensuring compliance with BAAQMD Regulation 9-1-304. The owner/operator will obtain a certification of the sulfur content of the coke for each delivery to assure compliance with this condition. The fuel certification records shall be retained on site for a minimum of five years from the date of entry and be made available to District representatives upon request. In the event the coke sulfur content exceeds 0.75 percent, the owner/operator shall arrange for a one time source test of S-1 at the time said coke is used to demonstrate that higher level of coke sulfur content will not produce gas stream emissions at A-12 baghouse that will exceed the limit established in BAAQMD Regulation 9-1-304.

If the sulfur dioxide emissions do not exceed the limit, the owner/operator shall be allowed to use coke with a sulfur content at or below the sulfur content of the coke used for the source test. In the event the coke sulfur content exceeds the new limit for coke sulfur content established in the source test, the owner/operator shall again arrange for a one time source test of S-1 at the time said coke is used to demonstrate that higher level of coke sulfur content will not produce gas stream emissions at A-12 baghouse that will exceed the limit established in BAAQMD Regulation 9-1-304.

The owner/operator shall notify the Source Test Group at the BAAQMD at least three days before any source test is performed. (basis: BAAQMD regulation 9-1-304, BAAQMD Regulation 2-6-501)

- 8. The owner/operator of S-1 shall maintain daily records of preventive maintenance inspections of A-12 baghouse. The preventive maintenance inspection reports shall be retained on site for a minimum of five years from the date of entry and be made available to District representatives upon request. (basis: BAAQMD regulation 6-301, BAAQMD Regulation 2-6-501)
- 9. The owner/operator of S-1 shall maintain weekly records of qualitative visible emissions data of A-12 baghouse using EPA Method 22. The records of visible emissions data shall be retained on site for a minimum of five years from the date of entry and be made available to District representatives upon request. (basis:

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VI. Permit Conditions (continued)

A. Source Specific Permit Conditions (continued)

BAAQMD regulation 6-301, BAAQMD Regulation 2-6-501)

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VI. Permit Conditions (continued)

A. Source Specific Permit Conditions (continued)

Condition #1783:

For S-4 Ductile Treating Station

- The sulfur dioxide emissions from S-4 shall not exceed 150 pounds per day. If
 the District determines that this SO2 emissions limit is exceeded, U.S. Pipe and
 Foundry shall install a District-approved dry SO2 Scrubbing system.
 (basis: BACT)
- 2. S-4 Ductile Treating Station shall be abated by A-10 whenever S-4 is charged with molten iron. (basis: cumulative increase)
- 3. The operator of A-10 shall install and maintain a mechanical gauge that reads the static pressure differential across the filter bags in inches water column. (basis: cumulative increase)
- *4. Dust collected in A-10 Baghouse must only be discharged into closed containers. (basis: BAAQMD Regulation 6-301)
- 5. The A-10 cloth filter bags must be cleaned or replaced when the pressure drop across the bags reaches 6 inches of water column. (basis: cumulative increase)
- 6. The owner/operator of S-4 shall maintain weekly records of preventive maintenance inspections of A-10 baghouse. The preventive maintenance inspection reports shall be retained on site for a minimum of five years from the date of entry and be made available to District representatives upon request. (basis: BAAQMD regulation 8-301, BAAQMD Regulation 2-6-501)
- 7. The owner/operator of S-4 shall maintain weekly records of qualitative visible emissions data of A-10 baghouse using EPA Method 22. The records of visible emissions data shall be retained on site for a minimum of five years from the date of entry and be made available to district representatives upon request. (basis: BAAQMD regulation 6-301, BAAQMD Regulation 2-6-501)

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VI. Permit Conditions (continued)

A. Source Specific Permit Conditions (continued)

Condition #2212:

For S-8 Bell Blow Out

- 1. S-8 shall not be operated unless it is abated by A-17 Baghouse. (basis: cumulative increase)
- 2. The cloth filter bags shall be cleaned when the pressure drop across the bags exceeds 6 inches water column. (basis: cumulative increase)
- 3. A mechanical gauge shall be installed so as to indicate, in inches water column, the static pressure differential across the bags. (basis: cumulative increase)
- 4. The owner/operator of S-8 shall maintain weekly records of qualitative visible emissions data of A-20 baghouse roof top emissions using EPA Method 22 or other related methods. The records of visible emission data shall be retained on site for a minimum of five years from the date of entry and be made available to District representatives upon request. (basis: BAAQMD regulation 6-301, BAAQMD Regulation 2-6-501)

Condition #14990

For S-15 Annealing Oven

1. The owner/operator of S-15 shall maintain monthly records of qualitative visible emission data of S-15 roof top emissions using EPA Method 22. The records of visible emissions data shall be retained on site for a minimum of five years from the data of entry and be made available to District representatives upon request. (basis: BAAQMD regulation 6-301, BAAQMD Regulation 2-6-501)

Condition #14991

For S-16 Pneumatic Cement Transport System and Plant

1. The owner/operator of S-16 shall maintain monthly records of qualitative visible emissions data of A9 baghouse using EPA Method 22 or other related method during cement delivery. The records of visible emissions data shall be retained on site for a minimum of five years from the date of entry and be made available to District representatives upon request. (basis: BAAQMD regulation 6-301,

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VI. Permit Conditions (continued)

A. Source Specific Permit Conditions (continued)

BAAQMD Regulation 2-6-501)

Condition #2676:

For S-32 Pneumatic Dust Transport System

- 1. S-32 shall not be operated unless it is abated by A-19 Baghouse. (basis: cumulative increase)
- 2. S-32 shall not be operated more than 11 hours per day. (basis: cumulative increase)
- 3. Particulate emissions from A-19 shall not exceed 0.10 grains per standard cubic foot. (basis: cumulative increase)
- 4. The Owner/operator of S-32 shall maintain the automatic shut down capabilities of Pneumatic Dust Transport System. (basis: BAAQMD regulation 6-301)

Condition #708:

For S-33 Gasoline Dispensing Facility (Non-Retail)

1. Pursuant to Regulation 8-7-112.7, this facility's annual gasoline throughput shall not exceed 60,000 gallons. (basis: BAAQMD Regulation 8-7-112.7)

Condition #13321:

For S-40 Portable Abrasive Blasting Unit #1

- 1. Gross abrasive blast media (sand) throughput at S-40 shall not exceed 12 tons during any consecutive twelve month period nor 243 pounds during any calendar day. (basis: cumulative increase)
- 2. United States Pipe and Foundry shall notify the District in writing in any blast media other than sand is utilized at S-40. (basis: cumulative increase)
- The owner/operator of S-40 shall maintain records of daily blast media throughput summarized on a monthly basis in a District-approved log. These records shall be retained on site for a minimum of five years from the date of

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VI. Permit Conditions (continued)

A. Source Specific Permit Conditions (continued)

entry and made available to District personnel upon request. (basis: cumulative increase, BAAQMD Regulation 2-6-501)

Condition #13321:

For S-41 Portable Abrasive Blasting Units #2

- 1. Gross abrasive blast media (aluminum oxide grit) throughput at S-41 shall not exceed 1.5 tons during any consecutive twelve month period nor 1000 pounds during any calendar day. (basis: cumulative increase)
- 2. United States Pipe and Foundry shall notify the District in writing in any blast media other than aluminum oxide grit is utilized at S-41. (basis: cumulative increase)
- 3. The owner/operator of S-41 shall maintain records of daily blast media throughput summarized on a monthly basis in a District-approved log. These records shall be retained on site for a minimum of five years from the date of entry and made available to District personnel upon request. (basis: cumulative increase, BAAQMD Regulation 2-6-501)

B. Facility-wide Permit Conditions

None

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VII. APPLICABLE EMISSION LIMITS & COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown, either annual (A), quarterly (Q), monthly (M), weekly (W), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

Table VII-A S-1 Cupola

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TSP	BAAQMD 6-301	N		Ringelmann No.1	BAAQMD cond #2274, Parts 4 and 5	С	temperature monitor, pressure drop monitor
	BAAQMD 6-305	Y		Fallout of visible particles	BAAQMD cond #2274, Parts 4 and 5	С	temperature monitor, pressure drop monitor
	BAAQMD 6-310	Y		0.15 gr/dscf	BAAQMD cond #2274, Parts 4 and 5	С	temperature monitor, pressure drop monitor
	BAAQMD 6-311	Y		40 lb/hr	BAAQMD cond #2274, Parts 4 and 5	С	temperature monitor, pressure drop monitor

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Final Permit for Facility #: A0083

Expiration Date: 7-1-02 ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Table VII-A (continued) **S-1 Cupola**

					7.7		
	Emission		Future		Monitoring	Monitoring	
	Limit	FE	Effective		Requirement	Frequency	Monitoring
Pollutant	Citation	Y/N	Date	Emission Limit	Citation	(P/C/N)	Туре
TSP	SIP 6-301	Y		Ringelmann No. 1	BAAQMD	С	temperature
					cond #2274,		monitor,
					Parts 4 and 5		pressure
							drop
							monitor
	SIP 6-301	Y		Ringelmann No. 1	BAAQMD	P/D	preventativ
					Cond #2274,		e
					Part 8		maintenanc
				_			e records
	SIP 6-301	Y		Ringelmann No. 1	BAAQMD	P/W	Visible
					Cond #2274,		emission
					Part 8		monitoring
SO_2	BAAQMD	N		GLC ¹ of 0.5 ppm for		N	
	9-1-301			3 min or 0.25 ppm for			
				60 min or 0.05 ppm			
				for 24 hours			
	BAAQMD	Y		sulfur emissions not	BAAQMD	P/E	Fuel
	9-1-302			to exceed 300 ppm,	condition		certification
				dry	#2274, part 7	P/E	;
							Source test
							when coke
							sulfur
							exceeds
							0.75%
	SIP	Y		Federal std: GLC ³ of			
	9-1-301			140 ppb, 24-hr			
				average, once/yr			
				and 30 ppb, annual			
				average			
				State std: GLC ³ of 40			
				ppb, 24-hr average,			
				and 250 ppb, 1 hr			
				average			

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

¹ Ground Level Concentration

Final Permit for Facility #: A0083

Expiration Date: 7-1-02 ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements

(continued)

Table VII-A (continued) **S-1 Cupola**

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
\$O2	BAAQMD Condition #2274, part	Y		Sulfur content of coke not to exceed 1.0%	BAAQMD condition #2274, part 7	P/E	Fuel certification
Lead	BAAQMD 11-1-301	Y		15 lb/day		N	
	BAAQMD 11-1-302	Y		glc ¹ not to exceed 1.0 ug/m ³ averaged over 24 hrs		N	

¹ Ground Level Concentration

Table VII-B S-4 Ductile Treating Station

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TSP	BAAQM D 6-301	N		Ringelmann No.1	BAAQMD cond #1783, Part 3	С	pressure drop monitor
	BAAQM D 6-305	Y		Fallout of visible particles	BAAQMD cond #1783, Part 3	С	pressure drop monitor
	BAAQM D 6-310	Y		0.15 gr/dscf	BAAQMD cond #1783, Part 3	С	pressure drop monitor
	BAAQM D 6-311	Y		40 lb/hr	BAAQMD cond #1783, Part 3	С	pressure drop monitor
	SIP 6-301	Y		Ringelmann No. 1	BAAQMD cond #1783, Part 3	С	pressure drop monitor

Final Permit for Facility #: A0083

Expiration Date: 7-1-02 ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Table VII-B (continued) **S-4 Ductile Treating Station**

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	S		iency	Monitoring Type		
TSP	SIP 6-301	Y		Ringelmann I	No. 1	BAAQMD	P/	W	preventative
						Cond #1783,			maintenance
						Part 6			records
	SIP 6-301	Y		Ringelmann I	No. 1	BAAQMD	P/	W	Visible
						Cond #1783,			emission
						Part 7			monitoring
Lead	BAAQM	Y		15 lb/day	,		N	1	
	D								
	11-1-301	***		or of				<u> </u>	
	BAAQM D	Y		GLC ¹ not to ex 1.0 ug/m ³ aver			N	N	
	11-1-302			over 24 hr					
SO_2	BAAQM	N		GLC ¹ of 0.5 ppr	n for 3		N		
	D			min or 0.25 pp					
	9-1-301			60 min or 0.05					
	0.1.202	***		for 24 hour				<u> </u>	
	9-1-302	Y		sulfur emission to exceed 300			N	N	
				dry	ppiii,				
	SIP	Y		Federal std: GI	LC^1 of		N	1	
	9-1-301			140 ppb, 24					
				average, once/					
				30 ppb, ann average	ual				
				State std: GLC	of 40				
				ppb, 24-hr ave					
				and 250 ppb,	1 hr				
	D 4 4 63 5	***		average				<u> </u>	
	BAAQM D	Y		150 lb/day	y		N	N	
	Condition								
	#1783,								
	part 2								

¹ Ground Level Concentration

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Table VII-C S-5, Ladle Lancing

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Li	mit	Monitoring Requirement Citation	Monit Frequ	iency	Monitoring Type
			Date			Citation	(P/C/N)		Турс
TSP	BAAQM	N		Ringelmann No.1			N	١	
	D								
	6-301								
	BAAQM	Y		Fallout of visible			N		
	D			particles					
	6-305								
	BAAQM	Y		0.15 gr/dscf			N		
	D								
	6-310								
	BAAQM	Y		40 lb/hr			N		
	D								
	6-311								
	SIP 6-301	Y		Ringelmann N	Vo. 1	BAAQMD	P/	D	preventative
						cond #14989,			maintenance
						Part 1			records
	SIP 6-301	Y		Ringelmann I	Vo. 1	BAAQMD	P/	W	Visible
						Cond #14989,			emission
						Part 2			monitoring

Final Permit for Facility #: A0083

Expiration Date: 7-1-02 ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Table VII-D S-8 Bell Blowout

	5-6 Den Diowott						
	Emission		Future		Monitoring	Monitoring	
	Limit	FE	Effective		Requirement	Frequency	Monitoring
Pollutant	Citation	Y/N	Date	Emission Limit	Citation	(P/C/N)	Туре
TSP	BAAQM	N		Ringelmann No.1	BAAQMD	С	pressure
	D				cond #2212,		drop
	6-301				Part 3		monitor
	BAAQM	Y		Fallout of visible	BAAQMD	С	pressure
	D			particles	cond #2212,		drop
	6-305			_	Part 3		monitor
	BAAQM	Y		0.15 gr/dscf	BAAQMD	С	pressure
	D				cond #2212,		drop
	6-310				Part 3		monitor
	BAAQM	Y		40 lb/hr	BAAQMD	С	pressure
	D				cond #2212,		drop
	6-311				Part 3		monitor
	SIP 6-301	Y		Ringelmann No. 1	BAAQMD	С	pressure
					cond #2212,		drop
					Part 3		monitor
	SIP 6-301	Y		Ringelmann No. 1	BAAQMD	P/W	Visible
					Cond #2212,		emission
					Part 4		monitoring

Table VII-E S-15 Annealing Oven

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TSP	BAAQM D 6-301	N	Date	Ringelmann No.1	Citation	N	Турс
	BAAQM D 6-305	Y		Fallout of visible particles		N	
	BAAQM D 6-310	Y		0.15 gr/dscf		N	

Final Permit for Facility #: A0083

Expiration Date: 7-1-02 ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

BAAQM	Y	40 lb/hr	N	
D				
6-311				

Table VII-E (continued) **S-15 Annealing Oven**

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TSP	SIP 6-301	Y		Ringelmann No. 1	BAAQMD	P/M	Visible
					cond #14990, Part 1		emission monitoring
SO_2	BAAQM	N		GLC ¹ of 0.5 ppm for 3		N	
	D			min or 0.25 ppm for			
	9-1-301			60 min or 0.05 ppm			
				for 24 hours			
	BAAQM	N		sulfur emissions not		N	
	D			to exceed 300 ppm,			
	9-1-302			dry			
	SIP	Y		Federal std: GLC ¹ of			
	9-1-301			140 ppb, 24-hr			
				average, once/yr and			
				30 ppb, annual av			
				State std: GLC ¹ of 40			
				ppb, 24-hr average,			
				and 250 ppb, 1 hr av			

¹ Ground Level Concentration

Table VII-F S-16 Pneumatic Cement Transport System

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TSP	BAAQM	N		Ringelmann No.1		N	
	D						
	6-301						
	BAAQM	Y		Fallout of visible		N	
	D			particles			
	6-305						

Final Permit for Facility #: A0083

Expiration Date: 7-1-02 ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

BAAQM	Y	0.15 gr/dscf		N	1	
D						
6-310						
BAAQM	Y	40 lb/hr		N	1	
D						
6-311						
SIP 6-301	Y	Ringelmann No. 1	BAAQMD	P/	M	Visible
			cond #14991,			emission
			Part 1			monitoring

Table VII-G S-17, Surface Coater

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	BAAQM D 8-19-302	Y		VOC limit of 2.8 lb/gal	8-19-501	P/W	coating records

Table VII-H S-32 Pneumatic Dust Transport System

	Emission Limit	FE	Future Effective		Monitoring Requirement	Monitoring Frequency	Monitoring
Pollutant	Citation	Y/N	Date	Emission Limit	Citation	(P/C/N)	Type
TSP	BAAQM	N		Ringelmann No.1		N	
	D						
	6-301						
	BAAQM	Y		Fallout of visible		N	
	D			particles			
	6-305						
	BAAQM	Y		0.15 gr/dscf		N	
	D						
	6-310						
	BAAQM	Y		40 lb/hr		N	
	D						
	6-311						
	SIP 6-301	Y		Ringelmann No. 1		N	

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

	BAAQM	Y	grain loading from	N	
	D		A-19 Baghouse not		
	Condition		to exceed 0.10		
	#2676,		gr/dscf		
	part 3				
Lead	BAAQM	Y	15 lb/day	N	
	D				
	11-1-301				
	BAAQM	Y	GLC1 not to exceed	N	
	D		1.0 ug/m³ averaged		
	11-1-302		over 24 hrs		

¹ Ground Level Concentration

Final Permit for Facility #: A0083

Expiration Date: 7-1-02 ID: DTJ

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Table VII-I

S-33 Gasoline Dispensing Facility (Non-Retail)

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQM	Y		95% (wt) organic		N	N
	D			vapor recovery			
	8-7-301.2			efficiency			
	BAAQM	Y		all vapor recovery		N	N
	D			equipment			
	8-7-301.6			maintained to be			
				leak-free and vapor			
				tight			

Table VII-J S-40 Portable Abrasive Blasting Unit #1 S-41 Portable Abrasive Blasting Unit #2

	Emission Limit	FE	Future Effective		Monitoring Requirement	Monitoring Frequency	Monitoring
Pollutant	Citation	Y/N	Date	Emission Limit	Citation	(P/C/N)	Type
TSP	BAAQM	Y		Ringelmann No. 1		N	
	D			Limitation			
	12-4-301						
	BAAQM	Y		Ringelmann No. 2		N	
	D			Limitation			
	12-4-302						

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

ID: DTJ

VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally found in Section 600 of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII - Applicable Emission Limits & Compliance Monitoring Requirements, of this permit.

Applicable		
Requirement	Description of Requirement	Acceptable Test Methods
SIP 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of
		Visible Emissions
BAAQMD	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of
6-301		Visible Emissions
BAAQMD &	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15,
SIP 6-310		Particulates Sampling
BAAQMD &	General Operations	Manual of Procedures, Volume IV, ST-15,
SIP 6-311		Particulates Sampling
BAAQMD &	Exemption, process subject to	Manual of Procedures, Volume IV, ST-7, Non-
SIP 8-1-110.3	Regulation 8, Rule 2 or 4	Methane Organic Carbon Sampling or
		EPA Method 25 or 25A.
BAAQMD &	Miscellaneous Operations	Manual of Procedures, Volume IV, ST-7, Non-
SIP 8-2-301		Methane Organic Carbon Sampling or
		EPA Method 25 or 25A.
BAAQMD	Exemption, Low Vapor	Manual of Procedures, Volume III, Method 28,
8-5-117	Pressure	Determination of Vapor Pressure of Organic
		Liquids from Storage Tanks
BAAQMD &	Phase I Requirements	Manual of Procedures, Volume III, Method 13,
SIP 8-7-301.1		Determination of the Reid Vapor Pressure of
		Petroleum Products
BAAQMD &	Phase I Requirements	Manual of Procedures, Volume IV, ST-36,
SIP 8-7-301.2		Gasoline Dispensing Facility Phase I Volumetric
		Efficiency
BAAQMD &	Phase I Requirements	Manual of Procedures, Volume IV, ST-30,
SIP 8-7-301.6		Gasoline Vapor Recovery Leak Test Procedure

Final Permit for Facility #: A0083 Expiration Date: 7-1-02

1 Date: 7-1-02 ID: DTJ

VIII. Test Methods (continued)

Applicable		
Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD	General Emission Limitation	Manual of Procedures, Volume IV, ST-19A,
9-1-302		Sulfur Dioxide, Continuous Sampling, or
		ST-19B, Total Sulfur Oxides Integrated Sample
BAAQMD &	Fuel Burning (Liquid and	Manual of Procedures, Volume IV, ST-19A,
SIP 9-1-304	Solid Fuels)	Sulfur Dioxide, Continuous Sampling, or
		ST-19B, Total Sulfur Oxides Integrated Sample
BAAQMD &	Daily Limitation, Lead	Manual of Procedures, Volume IV, ST-9, Lead
SIP 11-1-301		
SIP 12-4-301	Ringelmann 1 Limitations	Manual of Procedures, Volume I, Part 1,
		Evaluation of Visible Emissions
BAAQMD	Ringelmann 2 Limitations	Manual of Procedures, Volume I, Part 1,
12-4-302		Evaluation of Visible Emissions
BAAQMD &	Standard for abrasives before	Test Method No. California 371-A
SIP	blasting	
12-4-305.1		
BAAQMD &	Standard for abrasives after	Test Method No. California 371-A
SIP	blasting	
12-4-305.1		

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

IX. GLOSSARY

BAAQMD

Bay Area Air Quality Management District

BACT

Best Available Control Technology

Basis

The underlying authority which allows the District to impose requirements.

CAA

The federal Clean Air Act

CAAOS

California Ambient Air Quality Standards

CEOA

California Environmental Quality Act

CFR

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

CO

Carbon Monoxide

Cumulative Increase

The sum of permitted emissions from each new or modified source since a specified date pursuant to BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95). Used to determine whether threshold-based requirements are triggered.

District

The Bay Area Air Quality Management District

EPA

The federal Environmental Protection Agency.

Excluded

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

IX. Glossary (continued)

Not subject to any District Regulations.

Federally Enforceable, FE

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part 52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), and also including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

HAP

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by both 40 CFR Part 63, and District Regulation 2, Rule 5.

Major Facility

A facility with potential emissions of regulated air pollutants greater than or equal to 100 tons per year, greater than or equal to 10 tons per year of any single hazardous air pollutant, and/or greater than or equal to 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity as determined by the EPA administrator.

MFR

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Act and implemented by District Regulation 2, Rule 6.

MOP

The District's Manual of Procedures.

NAAQS

National Ambient Air Quality Standards

NESHAPS

National Emission Standards for Hazardous Air Pollutants. Contained in 40 CFR Part 61.

NMHC

Non-methane Hydrocarbons

NOx

Oxides of nitrogen.

NSPS

Standards of Performance for New Stationary Sources. Federal standards for emissions from

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

IX. Glossary (continued)

new stationary sources. Mandated by Title I, Section 111 of the Act, and implemented by both 40 CFR Part 60 and District Regulation 10.

NSR

New Source Review. A federal program for preconstruction review and permitting of new and modified sources of air pollutants for which the District is classified "non-attainment". Mandated by Title I of the Clean Air Act and implemented by 40 CFR Parts 51 and 52 as well as District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

Offset Requirement

A New Source Review requirement to provide federally enforceable emission offsets at a specified ratio for the emissions from a new or modified source and any pre-existing cumulative increase minus any on site contemporaneous emission reduction credits. Applies to emissions of POC, NOx, PM10, and SO2.

Phase II Acid Rain Facility

A facility that generates electricity for sale through fossil-fuel combustion and by virtue of certain other characteristics (defined in Regulation 2, Rule 6) is subject to Titles IV and V of the Clean Air Act.

POC

Precursor Organic Compounds

PM

Total Particulate Matter

PM10

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

PSD

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

SIP

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

IX. Glossary (continued)

SO₂

Sulfur dioxide

Title V

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

VOC

Volatile Organic Compounds

Units of Measure:

yr

=

bhp brake-horsepower Btu **British Thermal Unit** = grams g = gal gallon = horsepower hp hr hour = lb = pound in= inches maximum = max m^2 square meter = min minute = MM million = ppmv = parts per million, by volume parts per million, by weight ppmw =pounds per square inch, absolute psia pounds per square inch, gauge psig = standard cubic feet per minute scfm =

year

Final Permit for Facility #: A0083

Expiration Date: 7-1-02

ID: DTJ

X. APPENDIX A - STATE IMPLEMENTATION PLAN

See Attachment